QUADRE

TECHNOLOGY

- OUTSDANDING EFFICACY
- UNIFORM LIGHT OUTPUT
- IP43 PROTECTION
- OPAL, MICROPRISMATIC
- UGR<19

Quadre it's like a classic and essential piece to your wardrobe. Like a white shirt.

The low glare rating makes it fitted for workspaces where the lighting is necessary, but does not necessarily have to be acknowledged.

With the sun-like shine, it mimics natural light. By evenly spreading its luminosity, leaves no traces on the ground.

It's, more so, easy for mounting, and seamless when blended with modular ceilings.

DESIGN

- RECESSED ONLY FIXTURE
- METAL BODY
- LIGHTWEIGHT
- EASY TO FIT
- UNIFORMITY OF LIGHT EMISSION



For futher information about

REFLECTA® LED intelligent lighting solutions, please contact us at: M + 43 699 18 320 556 | T +43 463 27 60 05 | F +43 463 27 60 05 - 20 E sales@reflectaled.com

REFLECTA® GmbH

Parkring 2-6 A-8403 Lebring Austria EU www.reflectaled.com





TECHNICAL DATA

REFLECTA® QUADRE	
Mounting type	Recessed
Housing	Steel
Light source	LED
Optics	Opal, Microprismatic
Dimension	597 x 597 x 70 mm
Power	20 W, 45 W
Driver	Non-dimming, DALI
Main voltage	220 - 240V AC, 50 - 60 Hz
Power factor	$\lambda = 0.98$
Life expectancy	Up to 100.000 h L80B20
Lumen output (at 4000K)	From 2700 lm up to 6000 lm
Luminous efficacy	135 lm/W
Colour temperature	3000 K / 4000 K / 5000 K / TW
Colour rendering index	CRI>80, CRI>90
Ambient operating temperature	Ta= -5°C to +40°C
Emergency module	EM 1h, EM 3h
Protection	IP43
Colour finishing	White
Warranty	5 years
Made in	Slovenia (EU)