

REBUS

TECHNOLOGY

- OUTSTANDING ADAPTABILITY & FLEXIBILITY
- HIGH EFFICACY
- IP40 PROTECTION
- OPAL, MICROPRISMATIC, SPOT
- UGR<16 OR UGR<19

Rebus is a universal luminaire that works well as a stand-alone feature in small spaces, or office arrangements where light serves a particular purpose.

In light of modern architectural demands where the luminaire itself should not be visible, but should have a prominent lighting effect within the space, area, or for the demand it covers. Rebus is therefore a valuable pick for spaces where light plays a role in emphasizing the work done beneath it.

DESIGN

- ALUMINUM BODY
- THIN
- LINEAR
- ADAPTABLE
- MINIMALISTIC

REFLECTA

For further information about
REFLECTA® LED intelligent lighting solutions, please contact us at:
M + 43 699 18 320 556 | **T** +43 463 27 60 05 | **F** +43 463 27 60 05 - 20
E sales@reflectaled.com

REFLECTA® GmbH
Parkring 2-6
A-8403 Lebring
Austria EU
www.reflectaled.com





TECHNICAL DATA

REFLECTA® REBUS

Mounting type	Recessed, Ceiling, Suspended
Housing	Aluminum
Light source	LED
Optics	Opal, Microprismatic, Spot
Dimension	From 840 mm to 3100 mm
Power	From 10 W to 100 W
Driver	Non-dimming, DALI
Main voltage	220 - 240V AC, 50 - 60 Hz
Power factor	$\lambda = 0,98$
Life expectancy	Up to 100.000 h L80B20
Lumen output (at 4000K)	From 1100 lm up to 11000 lm
Luminous efficacy	Up to 125 lm/W
Colour temperature	3000 K / 4000 K / 5000 K / TW
Colour rendering index	CRI>80, CRI>90
Ambient operating temperature	Ta= -5°C to +40°C
Emergency module	EM 1h, EM 3h
Protection	IP40
Colour finishing	White, Black
Warranty	Regular 5 years, Extended option up to 10 years
Made in	Slovenia (EU)