

TECHNOLOGY

- LUMINOUS EFFICACY UP TO 166 lm/W
- EXTENDED OPERATING LIFETIME
- IP40, IP54, IP65 PROTECTION
- WIDE, MEDIUM, NARROW, ASYM, D-ASYM
- EXCELLENT HEAT MANAGEMENT

The industry also and especially deserves a light designed for its specific needs.

Fine industries can be categorized as industrial boutiques and should be treated that way too. That's where REW comes in.

It distinguishes itself by being RE(le)Wantly efficient and functional, adapting to the higher demands of lofty ceilings. Easy to install, with a prompt return on investment.

DESIGN

- ALUMINUM BODY
- LIGHTWEIGHT
- STRONG AND STABLE STRUCTURE
- LINEAR
- VERSATILE
- INNOVATIVE

REFLECTA

For further information about
REFLECTA® LED intelligent lighting solutions, please contact us at:
M + 43 699 18 320 556 | **T** +43 463 27 60 05 | **F** +43 463 27 60 05 - 20
E sales@reflectaled.com

REFLECTA® GmbH
Parkring 2-6
A-8403 Lebring
Austria EU
www.reflectaled.com





TECHNICAL DATA

REFLECTA® REW

Mounting type	Ceiling, Suspended
Housing	Aluminum
Light source	LED line SMD 3R
Optics	Wide, Medium, Narrow beam, Asymmetric, Double asymmetric
Dimension	From 900 mm to 3360 mm
Power	From 30 W to 240 W
Driver	Non-dimming, DALI
Main voltage	220 - 240V AC, 50 - 60 Hz
Power factor	$\lambda = 0,98$
Life expectancy	Up to 100.000 h L80B20
Lumen output (at 4000K)	From 4640 lm up to 34300 lm
Luminous efficacy	Up to 166 lm/W
Colour temperature	4000 K / 5000 K
Colour rendering index	CRI>80
Ambient operating temperature	Ta= -30°C to +55°C
Emergency module	EM 1h, EM 3h
Protection	IP40, IP54, IP65
Colour finishing	White, Black, Custom RAL on request
Warranty	Regular 5 years, Extended option up to 10 years
Made in	Slovenia (EU)