REWOOD

TECHNOLOGY

- ONE OF A KIND
- NATURAL MATERIALS
- EFFICIENT
- OPAL, MICROPRISMATIC, SPOT
- UGR<16 OR UGR<19

With a series of wooden luminaires, we've taken sustainability to a new level. The exterior is made of a solid, fully recyclable oak, making each luminaire a story of its own.

The wood that you see is the one that you get.

The design is perfectly fit for offices from those within the intimate shelter of private homes to corporate buildings, where its soft, natural appearance adds an additional warm, homey impact.

DESIGN

- WOODEN BODY
- SUSTAINABLE
- LINEAR
- DIFFERENT WOOD TYPES
- **INNOVATIVE**

REFLECTA =

For futher information about

REFLECTA® LED intelligent lighting solutions, please contact us at: M + 43 699 18 320 556 | **T** +43 463 27 60 05 | **F** +43 463 27 60 05 - 20 **E** sales@reflectaled.com

REFLECTA® GmbH

Parkring 2-6 A-8403 Lebring Austria EU www.reflectaled.com









TECHNICAL DATA

| REFLECTA® REWOOD | |
|-------------------------------|--|
| Mounting type | Ceiling, Suspended with direct/indirect light emission |
| Housing | Aluminum, Natural oak |
| Light source | LED |
| Optics | Opal, Microprismatic, Spot |
| Dimension | 1150 mm, 1430 mm |
| Power | From 15 W to 56 W |
| Driver | Non-dimming, DALI |
| Main voltage | 220 - 240V AC, 50 - 60 Hz |
| Power factor | $\lambda = 0.98$ |
| Life expectancy | Up to 60.000 h L80B20 |
| Lumen output (at 4000K) | From 1500 lm to 7150 lm |
| Luminous efficacy | Up to 146 lm/W |
| Colour temperature | 3000 K / 4000 K / 5000 K / TW |
| Colour rendering index | CRI>80, CRI>90 |
| Ambient operating temperature | Ta= 0°C to +30°C |
| Emergency module | / |
| Protection | IP40 |
| Colour finishing | Natural oak, Custom on request |
| Warranty | 5 years |
| Made in | Slovenia (EU) |